

Expand your wireless coverage with MIMO!



RangePlus Wireless Network USB Adapter

Model: WUSB100

PRODUCT DATA

High-speed, long-range, wireless networking for your desktop or notebook computer

MIMO smart antenna technology captures faint signals for extended range and reduced dead spots

Much faster than Wireless-G when connected to RangePlus or Wireless-N, but also works great with Wireless-G and -B devices

Advanced wireless security: Wi-Fi Protected Access™ (WPA2) with up to 256-bit encryption

PRODUCT DATA

Features

- Much faster than Wireless-G, but can also connect to Wireless-N, -G and -B networks
- Complies with Wireless-B (802.11b) and Wireless-G (802.11g) standards
- Supports WEP (64- and 128-bit), WPA and WPA2 (Personal and Enterprise) encryption security
- Compatible with Microsoft Windows 2000 (SP4), XP (SP2 or later) and Vista

RangePlus Wireless Network USB Adapter

The RangePlus Wireless Network USB Adapter is the simple way to add or upgrade wireless connectivity in your desktop or notebook computer. Just plug it into your computer's USB port and enjoy incredible high-speed wireless network access while retaining true mobility.

The RangePlus Wireless Notebook Adapter uses the very latest wireless networking technology to achieve extended range. Unlike ordinary wireless networking technologies that are confused by signal reflections, MIMO actually uses these reflections to increase the range and reduce "dead spots" in the wireless coverage area. The robust signal travels farther, maintaining wireless connections much farther than standard Wireless-G. And with MIMO, the farther away you are, the more speed advantage you get. It works great with standard Wireless-G and -B equipment, but when both ends of the wireless link use RangePlus technology, the throughput can be increased even more by using twice as much radio band.

Once you're connected, you can keep in touch with your e-mail, access the Internet, and share files and other resources such as printers and network storage with other computers on the network, wherever you wander. At home, you can surf the web or use instant messaging to chat with friends while sitting out on the patio. You'll also be able to connect with any of the growing number of public hotspots springing up in coffee shops, airport lounges, hotels and convention centers. Your wireless connection is protected by industrial-strength WPA2 encryption. The included Setup Wizard will walk you through configuring the adapter to your network's settings, step by step.

Get connected with fast throughput, reduced dead spots, and increased wireless range with the RangePlus Wireless Network USB Adapter from Linksys.

PRODUCT DATA

RangePlus Wireless Network USB Adapter

Specifications

Model WUSB100

Standards IEEE 802.11b, IEEE 802.11g

LEDs Power/Link/Act # of Antennas 2 Internal Antennas

Connector Type USE

Modulations 802.11b; CCK, OPSK, BPSK

802.11g: 64-QAM, 16-QAM

802.11n draft: BPSK, QPSK, 16-QAM, 64-QAM

RF Power (EIRP) in dBm 802.11b: 17.6 dBm

802.11g: 17.2 dBm 802.11n: 17.1 dBm

Antenna Gain in dBi 2 dBi

Power Consumption TX: 590mA, HT20, MCS7; 610mA, HT40, MCS7 at 3.3V

RX: 480mA, HT20, MCS15; 570mA HT40, MCS15 at 3.3V

Security Features WEP, Wi-Fi Protected Access™ 2 (WPA2)

Security Key Bits Up to 256-Bit Encryption

Environmental

Dimensions 3.86" x 0.39" x 1.1" (98 x 10 x 28 mm)

Weight 0.6 oz (17 g)

Power 3.3V

Certification FCC, UL, CB, CE

Operating Temp. 32 to 104°F (0 to 40°C)
Storage Temp. 14 to 158°F (-10 to 70°C)
Operating Humidity 10 to 85%, Noncondensing
Storage Humidity 5 to 90%, Noncondensing

Package Contents

- · RangePlus Wireless USB Adapter
- USB Stand
- · Setup CD-ROM
- · User Guide on CD-ROM
- · Quick Installation Guide

Minimum Requirements

- · 600 MHz or Faster PC
- · 256 MB of RAM Memory
- · CD-ROM Drive
- Available USB Slot
- Up-to-Date Windows 2000, XP or Vista

The maximum performance for wireless is derived from IEEE Standard 802.11 specifications. Actual performance can vary, including lower wireless network capacity, data throughput rate, range and coverage. Performance depends on many factors, conditions and variables, including distance from the access point, volume of network traffic, building materials and construction, operating system used, mix of wireless products used, interference and other adverse conditions.

Check the product package and contents for specific features supported. Specifications are subject to change without notice and the product package and contents for specific features supported. Specifications are subject to change without notice and the product package and contents for specific features supported. Specifications are subject to change without notice and the product package and contents for specific features supported. Specifications are subject to change without notice and the product package and contents for specific features supported. Specifications are subject to change without notice and the product package and contents for specific features supported. Specifications are subject to change without notice and the product package and the produc



Linksys is a registered trademark or trademark of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries. Copyright © 2007 Cisco Systems, Inc. All rights reserved. Other brands and product names are trademarks or registered trademarks of their respective holders.

50 countries, supported by 12 Linksys Regional Offices throughout the world. For a complete list of local Linksys Sales and Technical Support contacts, visit our worldwide website at

Linksys products are available in more than

A Division of Cisco Systems, Inc. 121 Theory Irvine, CA 92617 USA

www.linksys.com

E-mail: sales@linksys.com

www.linksys.com

Web:

7102510NC-JL Model: **WUSB100**